

STREET SCOOTER

Spykstaal


STREETSCOOTER BY SPIJKSTAAL

100% ELECTRIC

SPIJKSTAAL INTERNATIONAL B.V. IS PART OF THE PEINEMANN MOBILFT GROUP AND A LEADING COMPANY IN OFFERING ELECTRIC MOBILITY. SINCE 2017 SPIJKSTAAL SELLS AND RENTS THE STREETSCOOTER; A 100% ELECTRIC VEHICLE THAT IS ABLE TO DRIVE ON THE PUBLIC ROAD.

BENEFITS OF THE STREETSCOOTER

- 100% electric drive
- 100% emission-free
- Tough commercial vehicle for everyday use
- Individually configurable
- Complete solution with charging infrastructure
- Low operating costs thanks to hard-wearing components
- High, efficient load volume
- Ergonomic construction
- Electric window winders for added comfort
- Heated windscreen for extra safety



STREETSCOOTER!



STREETSCOOTER

WORK (20 kWh or 40 kWh)

STANDARD SPECIFICATIONS

Maximum Speed	85 km/h
Range 20kWh / 40kWh	118 km (NEFZ); 80 km (Post) / 232km (NEFZ)
Motor	Permanent Magnet Synchronous Motor (PMSM)
Gear Type	Single-stage differential gearbox
Drive Type	Front wheel drive
Peak power / Continuous power	48 kW / 38 kW
Battery	Lithium-ion
Battery capacity	20 kWh or 40 kWh
Charger	Charging station (230V, single-phase 16A)
Charging time	4,5 hours (0-80%); 7 hours (0-100%)
Airbag	Driver airbag as standard
Steering	Electro hydraulic power-assisted steering
ESC	As standard (electronic stability control)

STREETSCOOTER WORK BOX

Tare Weight	1.440 kg
Permissible total weight	2.180 kg
Total load capacity	740 kg
Usable volume of box	4,3 m ³
Length / breadth / height	4.709 / 2.087 / 2.039 mm

STREETSCOOTER WORK PICKUP

Tare Weight	1.460 kg
Permissible total weight	2.180 kg
Total load capacity	720 kg
Length / breadth / height	4.741 / 2.087 / 1.859 mm
Structure outside of pickup(L/B/H)	2.127 / 1.807 / 600 mm
Structure inside of pickup (L/B/H)	2.130 / 1.759 / 400 mm

STREETSCOOTER WORK PURE

Tare Weight	1.280 kg
Permissible total weight	2.180 kg
Total load capacity	900 kg
Length / breadth / height	4.676 / 2.087 / 1.861 mm

WORK BOX



WORK PICKUP



WORK PURE



STREETSCOOTER

WORK L (40 kWh)

STANDARD SPECIFICATIONS

Maximum speed	85 km/h
Range	205 km (NEFZ)
Motor	Permanent Magnet Synchronous Motor (PMSM)
Gear Type	Single-stage differential gearbox
Drive Type	Front wheel drive
Peak power / Continuous power	48 kW / 38 kW
Battery type	Lithium-ion
Battery capacity	40 kWh
Charger	Charging station (230V, single-phase 16A)
Charging time	10 hours (0-80%); 13 hours (0-100%)
Airbag	Driver airbag as standard
Steering	Electro hydraulic power-assisted steering
ESC	As standard (electronic stability control)

STREETSCOOTER WORK L BOX

Tare Weight	1.695 kg
Permissible total weight	2.600 kg
Total load capacity	905 kg
Usable volume of box	8 m ³
Length / Breadth / Height	5.784 / 2.087 / 2.347 mm
Structure outside of box (L/B/H)	3.250 / 1.820 / 1.485 mm
Structure inside of box (L/B/H)	3.150 / 1.675 / 1.407 mm

STREETSCOOTER WORK L PICKUP

Tare Weight	1.715 kg
Permissible total weight	2.600 kg
Total load capacity	885 kg
Length / Breadth / Height	5.840 / 2.087 / 2.000 mm
Structure outside of pickup (L/B/H)	3.300 / 1.810 / 592 mm
Structure inside of pickup (L/B/H)	3.177 / 1.757 / 400 mm

STREETSCOOTER WORK L PURE

Tare Weight	1.465 kg
Permissible total weight	2.600 kg
Total load capacity	1.135 kg
Length / breadth / height	5.784 / 2.087 / 1.867 mm

WORK L BOX



WORK L PICKUP



WORK L PURE



STREETSCOOTER EQUIPMENT

INTERIOR

- Infotainment system (radio, bluetooth hands-free equipment, rear view camera, navigation system)
- Heated seats
- Rear window (Pickup)
- Roof interior trim with interior courtesy light
- Centre console with storage options
- 12V connection
- Multiple storage spaces in the interior
- Water-repellent foot area coating
- Multi-adjustable driver's seat

FUNCTIONAL EQUIPMENT

- Heating (electric)
- Dust filter
- Anti-condensation nozzles windscreen
- Windscreen heating
- Recirculation function
- One-touch indicator (3 x)
- Steering wheel adjustable as to height and length
- Central locking system including remote control
- Electric window (on both sides)
- Electric exterior mirror adjustment (on both sides)
- Windscreen wiper H7 with height adjustment for pressure distribution balance
- Basic LED package (front blinkers in LED technology, LED navigation light in front as well as LED brake light)
- Side indicator

SAFETY EQUIPMENT

- ABS
- ESC (only WORK)
- Power assisted steering
- Three-point seat belt (on both sides)
- Seat belt warning system & seat belt pretensioner
- Driver airbag

INSTRUMENT CLUSTER

- Instrument use with digital speed display
- Trip display, time
- Optical and acoustic road-ready display (drive ready)
- Displays for travel modes, charge level, range and service information





Spijkstaal International B.V.

Mandemakerstraat 150-152
3194 DG Hoogvliet
The Netherlands

T +31 (0)181 45 70 30

E info@spijkstaal.nl

www.spijkstaal.nl