



PEINEMANN

EQUIPMENT



Scissorlift TLE



Operation from a safe distance by remote control

Extends to 6m (20ft) height

Easy access into channel heads

Minimum working height 0.70m (2ft/4")

TLE drive pulls lances at the front

Cleans bundles up to 6m high without scaffolding

Optional wireless remote control

Scissorlift TLE

The hydraulically driven rigid lance machine is capable of operating 3 or 5 lances. Built on a double scissorlift platform, the machine is capable of cleaning exchanger tubes in place up to 6 meter (20 feet) high. This eliminates the need to build scaffolding and saves time.

The machine is easily transported on a trailer and comes complete with it's own diesel driven engine. A powerful drive mechanism at the front pulls lances into the exchanger to

avoid damage to the lances. The machine is equipped with a 50 foot wired remote and a wireless remote controller is optional.

The average cleaning speed is 300 – 500 tubes per hour.

High pressure water connections are M36x2, or Medium Pressure Autocalve 1" up to 1,500 bar. The system is driven by a Hatz diesel engine type 1D81C/8,6 Kw pump Sauer 11CC.



PEINEMANN

EQUIPMENT

Scissorlift TLE

Technical specifications

- Working height
min. 0,70 m / 27.58 inch
- Working height
max. 6,00 m / 19.7 ft
- Working length
standard 6,1 m / 20 ft
8,1 m / 26.8 ft
- Bundle \varnothing
max. 1,60 m / 63.04 inch
- Lance speed
00 - 0,5 m/sec / 00 - 19.7 inch/sec
- Number of lances
3 or 5 pieces
- Engine
Silent pack HATZ diesel Mod. ID18C
- Horse power
11 hp at 2.400 Rpm
- Cooling system
Air
- Hydraulic system
Hydraulic pump 11 cc
- Weight
 \pm 2.400 kg / 5,291 lbs
- Length
standard 8.177 mm * / 26.85 ft
10.177 mm / 42.46 inch
- Width
2.192 mm / 86.36 inch

* The machine comes equipped with one extension,
2 meters long, so you can use 10 meter lances.

Peinemann Equipment

See also
www.peinemannequipment.com

Peinemann Equipment B.V.

Nieuwe Langeweg 40
3194 DB Hoogvliet
Phone: +31(0)10 - 295 50 00
Fax: +31(0)10 - 295 50 49

Peinemann USA

22820 I-H 45 N., Bldg #7, Ste P
Spring, TX 77373
Phone: 281-288-7979
Fax: 866-431-5140

E-mail: info@peinemann.nl
Website: www.peinemannequipment.com